



ELECTRICAL CHARACTERISTICS :

1. IMPEDANCE : 270 Ω M + <750 Ω M // 150 nF)
2. DCR : EACH LINE = 25 Ω M MAX.
3. INSERTION LOSS : 1KHZ = 1.3 dB MAX.
4. INSERTION LOSS DISTORTION : 200HZ = ± 1 dB,
3.4KHZ = ± 1 dB.
5. RETURN LOSS : 300HZ = 14 dB MIN.
500HZ = 18 dB MIN.
2KHZ = 18 dB MIN.
3.4KHZ = 14 dB MIN.
6. ATTENUATION : 30KHZ = 45 dB MIN.
100KHZ = 45 dB MIN.
200KHZ = 45 dB MIN.
1.1MHZ = 45 dB MIN.

						Atech [®]		TITLE ADSL CO SPLITTER	
						Atech Technology Co., Ltd.		DWG. NO. ATF075	
						TEL: (02)2794-6667 FAX: (02)2794-8804			
A	SPEC. & DIM.	03/24 /2004	BART	EUGENE	SUEDY	UNITS: M/M		SAFETY	
	RELEASE	03/22 /2004	BART	SIMON	SUEDY			SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>	
REVISIONS						03/22/04			